

FEB 13 2009

Feb 13 2009 6:30PM HP LASERJET FAX

P. 1

PTO/SB/97 (01-09)

Approved for use through 02/28/2008. OMB 0551-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Certificate of Transmsslon under 37 CFR 1.8

I hereby certify that this correspondence is being facsimile transmitted to the United States Patent and Trademark Office

February 13, 2009
on _____
Date



Signature

Roseanna Kaplan

Typed or printed name of person signing Certificate_____
202-419-7000_____
Registration Number, if applicable_____
Telephone Number

Note: Each paper must have its own certificate of transmission, or this certificate must identify each submitted paper.

Response to Notification of Non-Compliant Appeal Brief
(Serial No. 10/539,293 :- Docket No. 7863-84347)

This collection of information is required by 37 CFR 1.8. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1.8 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1460, Alexandria, VA 22313-1460. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1460, Alexandria, VA 22313-1460.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

FEB 13 2009

PATENT
7863-84347IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES

Applicants: Johannes BRUSKE et al. Confirmation: 7521
Serial No.: 10/539,293 Group Art Unit: 3785
Filed: June 16, 2005 Examiner: R. H. Muromoto, Jr.
For: SHAFT FRAME AND HEDDLE SHAFT FOR POWER LOOMS

RESPONSE TO NOTICE

Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313-1450

February 13, 2009

Sir:

In response to the Notification of Non-Compliant Appeal Brief dated January 13, 2009, please substitute the attached Summary of the Claimed Subject Matter for that included in the Brief filed December 8, 2008.

Respectfully submitted,
FITCH, EVEN, TABIN & FLANNERY


Norman N. Kunitz, #20,588

Customer No. 42798
One Lafayette Centre
1120 - 20th Street, NW, Suite 750, South
Washington, DC 20036
(202) 419-7000 (telephone)
(202) 419-7007 (telecopier)
NNK:rk

Attorney Docket No. 7863-84347

Feb 13 2009 6:30PM HP LASERJET FAX

p. 3

FEB 13 2009

Serial No. 10/539,293

SUMMARY OF CLAIMED SUBJECT MATTER

The present invention is directed to a shaft frame for a power loom having a novel heddle support rail. As shown, for example in Fig. 1 of the present application, such shaft frames (2) which is moved back and forth at a high speed, are normally provided with two spaced parallel support rails (7, 8), on which a plurality of heddles (3) are mounted, with each of the rails extending into a respective eyelet (5, 6) formed in the head or end of each heddle, as described in paragraph 26 of the present application. In modern day power looms, the accelerations and braking forces during the back and forth movement are so great that the heddles (3), which as a rule are held with some play on the shaft frame (2), hit their bearings and dig in there. This process generates noise and wear and puts limits on the operating speed of a power loom. Accordingly, it is desirable to reduce the play between the heddles and the support rails (see paragraphs 3-6 of the present application).

According to the presently claimed invention as defined in each of the independent claims 7-9, this reduction in play is achieved by providing the shaft frame with a novel heddle support rail (7) as shown in Figs 4-7 of the present application.

According to the embodiment of the invention shown in Figs. 4 and 5, and defined in claim 7, at least one of the two heddle support rails (7, 8) is itself comprised of two rail portions (7a and 7b) formed as two resilient spring legs that point away from each other, i.e., extend in opposite directions, as discussed in paragraph 42. The two rail portions (7a and 7b) both extend into a single end

Serial No. 10/539,293

eyelet (5) of a heddle (3), as can clearly be seen in Fig. 5, in order to support a heddle in a resilient manner. The two rail portions or spring legs (7a, 7b) are each generally C-shaped and are disposed symmetrically to one another relative to a horizontal plane (H) as can be seen in Fig. 4 and as described in paragraph 42.

Alternatively, according to the embodiment of Fig. 7, as defined in claim 9, at least one of the heddle support rails (7, 8), i.e., the heddle support rail 7, is divided into two parts (51, 55) which are diametrically opposed to one another and supported on the beam (46) connected to the frame (2). One part (51) is rigidly supported on the beam (46), and the other part (55) is movably supported on the beam (46) against the force of a compression spring (58) as described in paragraph 44 of the present application. The two parts or portions (51, 55) of the support rail are each a jib or support for insertion into a single end eyelet of a heddle. As can be seen in Fig. 7, the two parts (51, 55) are each generally U-shaped, with each having its longer leg, e.g., leg 53 of part 55, supported on the beam (46). As can be appreciated, the spring (58) will tend to spread the two parts (51, 55) apart in order to engage the interior of the end eyelet of the heddle and thus reduce any play.

Independent claim 8 is an original claim and is generic to both of the embodiments shown in Figs. 4-7. This claim recites that the support rail 7 be formed of two jibs or parts 7a, 7b as shown in Figs. 4 and 5 and described in paragraphs 42 and 43, or members 51, 52 as shown in Fig. 7 and described in paragraphs 44 and 45. As can be seen in the figures and as described, the two

Serial No. 10/539,293

jibs or members 7a, 7b and 51, 52 are diametrically opposed from one another and are received in a single eyelet 5 of a heddle 3. The two opposed receiving jibs or parts 7a, 7b or 51, 52 are tensed resiliently away from each other as described in paragraphs 43-45 as a result of the oppositely directed spring legs 7a, 7b of Fig. 4 or by the spring 56 of Fig. 7 so that they receive the heddle eyelet without play..

Both embodiments of the single heddle support rail according to the Figs 4-7 of the present application, and which extend into a single end eyelet of a heddle, will dampen impacts and shocks created by the heddles moving on the heddle rail due to sharp acceleration and deceleration during operation.